

# PremierLabellers



## P120 3-Roller Wrap

The Premier 120 3-Roller Wrap has been designed to handle almost every type of medium and high speed wraparound label applications.

Capable of applying a single full wrap label or two labels in orientation to each other around the circumference of the product using our innovative 3-roller system.

# PremierP120 3-Roller Wrap

The proven Premier P100 stepper driven label head and 3 roller system ensures single or with our optional orientation system, two labels can be positioned and applied with extreme precision at speeds upto 80/min.



Almost any type of round container in glass or plastic can be labelled accurately with our 3 roller system. Ideally suited to the food, pharmaceutical, healthcare, household and cosmetics industries.



Our Siemens PLC control system incorporates a touchscreen HMI for all setting-up, operation and diagnostic functions of the P120. The simple to operate software will store up to 500 product recipes for quick and easy changeovers and set-ups.



## Features

- GAMP 5 standard
- Stepper driven label head
- Variable speed conveyor
- Siemens PLC control system
- TFT Touchscreen HMI
- 125mm web height kit

## Technical Data

Container width/diameter	Upto 150mm*
Container height	Upto 300mm*
Conveyor width	83mm / 115mm / 150mm
Label height	10mm - 125mm / 210mm
Label length	10mm - 200mm*
Label Reel Size	300mm Ø / 76mm core
Max Speed	Upto 35m/min
Electrical	230V single phase 50/60Hz
Compressed air	60/80psi 6 bar
Overall Dimensions (LxWxH)	1500mm x 955mm x 1350mm
Operating height	850mm - 915mm / 910mm - 975mm
Weight	Approx 200Kg

\* For special applications, please contact us for more information.

## Options

- Integrated thermal transfer printer
- Integrated hot foil coder/embosser
- 115mm / 150mm wide conveyor
- 210mm extended height web kit
- Integrated inspect/reject systems
- Spotting / print registration
- Setting scales & dials
- Interlocked guarding to CE standards