


SL-404 VANILLA

RENAISSANCE I Lychee DUAL TONE TEXTURE





SL-413 RYE*

SL-472 WOODLAND

SL-422 HONEY*



lychee

renaissance i

nature friendly, naturally soft

RENAISSANCE I



DUAL TONE TEXTURE

:: SPECIFICATIONS

. Width: 54"

Nominal total thickness: .036 gauge
Standard weight: 21 oz / linear yard
Content: Face: 100% polyurethane
Back: 100% reinforced Pollex

Il Langth: 50 yards

. Roll Roll Length: 50 yards

:: FLAMMABILITY REQUIREMENTS*

- . CA Bulletin 117 Class 1
- . UFAC Class 1
- . NFPA 260 Class 1
- . BIFMA Class A
- . IMO A.652(16) 8.2
- . Can be treated to meet FAR Specifications
- *This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

:: CARE & CLEANING

- . General Care: While this product is inherently stain resistant, it is important to keep it clean at all times to maintain the original look and the rich feel.
- . Stain Removal: Spot cleaning with soap and water will remove most of the everyday stains without leaving any stain of color behind. Tough, stubborn stains can be removed by a mild cleaning fluid followed by clean water rinse.

:: REVOLUTION IN FAUX LEATHER LUXURY

- . Nature friendly, PVC free product.
- . Contains no volatile compounds which are found in most vinyl-based products.
- Supple leather touch with exceptional
- strength and performance.
- Controlled 4-way stretch for excellent tailorability.

:: GENERAL CHARACTERISTICS

- . Superior wear resistance (ASTM D3597 Wyzenbeek) Exceeds 100,000 double rubs by wire screen
- Colorfastness to light (AATCC-16/400 hours)
- . Colorfastness to cracking (AATCC-8/passes)
- . Colorfastness to chlorine bleach (AATCC-3) passes 1:10 & 1:5 bleach dilution test
- . Yarn slippage (ASTM D4034/passes)
- . Excellent breaking strength (ASTM D5034)
- Excellent tear strength (ASTM D2262)
- . Cold crack resistant
- . Mildew resistant backing

:: SUITABLE APPLICATIONS

- . Contract interiors
- . Office
- . Restaurant
- . Hospitality
- . Healthcare
- . RV/Marine Interiors



FLOCK TEX, Inc. 200 Founders Dr. Woonsocket, RI 02895

Tel: 401.765.2340 Fax: 401.765.4915 Toll Free: 800.556.7286

www.flocktex.com