




SP-232 WALNUT



SP-201 CLOUD


RENAISSANCE I

provençe


GLAZED VINTAGE LEATHER



SP-221 CANARY



SP-231 BUCK




SP-232 WALNUT



SP-241 FIRE RED



SP-242 MERLOT




SP-243 BORDEAUX



SP-252 DEEP FOREST




SP-251 PARSLEY



SP-281 ULTRA MARINE



SP-233 JAVA



SP-234 ESPRESSO



SP-291 BLACK

Printed colors shown are extremely accurate to the actual colors however please request a memo sample to ensure satisfaction.

RENAISSANCE I
provenCe
GLAZED VINTAGE LEATHER

RENAISSANCE I

provenCe

:: SPECIFICATIONS

- . Width: 54"
- . Nominal total thickness: .044 gauge
- . Standard weight: 16 oz / linear yard
- . Content: Face: 100% polyurethane
Back: reinforced Polyester
- . Roll length: 50 yards

:: FLAMMABILITY REQUIREMENTS*

- . FMVSS-302
 - . CA Bulletin 117 Class 1
 - . UFAC - Class 1
 - . NFPA 260 - Class 1
 - . BIFMA - Class A
 - . IMO A.652(16) 8.2
 - . Can be treated to meet FAR Specifications
- *This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

:: CARE & CLEANING

- . General Care: While this product is inherently stain resistant, it is important to keep it clean at all times to maintain the original look and the rich feel.
- . Stain Removal: Spot cleaning with soap and water will remove most of the everyday stains without leaving any stain or color behind. Tough, stubborn stains can be removed by a mild cleansing fluid followed by clean water rinse.

GLAZED VINTAGE LEATHER

:: NATURE FRIENDLY, NATURALLY SOFT

- . Nature friendly, PVC free product
- . Contains no volatile compounds which are found in most vinyl-based products.
- . Supple leather touch with exceptional strength and performance.

:: GENERAL CHARACTERISTICS

- . Superior wear resistance (ASTM D3597 Wyzenbeek) Exceeds 100,000 double rubs by wire screen
- . Colorfastness to light (AATCC-16/400 hours)
- . Colorfastness to crocking (AATCC-8/passes)
- . Colorfastness to chlorine bleach (AATCC-3) passes 1:10 & 1:5 bleach dilution test
- . Yarn slippage (ASTM D4034/passes)
- . Excellent breaking strength (ASTM D5034)
- . Excellent tear strength (ASTM D2262)
- . Cold crack resistant

:: SUITABLE APPLICATIONS

- . Contract interiors
- . Office
- . Restaurant
- . Hospitality
- . Healthcare
- . RV/Auto/Marine interiors



FLOCK TEX, Inc.
200 Founders Dr.
Woonsocket, RI 02895
Tel: 401.765.2340
Fax: 401.765.4915
Toll Free: 800.556.7286
www.flocktex.com