


PYRITE

Murano

RENAISSANCE II

nature friendly, naturally soft




AZURE



ICY CORAL




GOLD DUST




ANTIQUE GOLD



BRASS




TOURMALINE




BRONZE



*COPPER KETTLE



BLACK PEARL



*PEWTER

Printed colors shown are extremely accurate to the actual colors however please request a memo sample to ensure satisfaction.



Murano

RENAISSANCE II

nature friendly, naturally soft

RENAISSANCE II

nature friendly, naturally soft

:: SPECIFICATIONS

- . Width : 54"
- . Nominal total thickness : .048 gauge
- . Standard weight : 14 oz / square yard
- . Content : Face: 100% polyurethane
Back: polyester/cotton blend
- . Roll length : 40 yards

:: FLAMMABILITY REQUIREMENTS*

- . FMVSS-302
- . CA Bulletin 117 Class 1
- . UFAC-Class 1
- . Can be treated to meet FAR Specifications
*This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

:: CARE & CLEANING

- . General Care: While this product is inherently stain resistant, it is important to keep it clean at all times to maintain the original look and the rich feel.
- . Stain Removal: Spot cleaning with soap and water will remove most of the everyday stains without leaving any stain or color behind. Tough, stubborn stains can be removed by a mild cleansing fluid followed by clean water rinse.

Murano

:: NATURE FRIENDLY, NATURALLY SOFT

- . Innovative non-PVC product
- . Contains no volatile compounds which are found in most vinyl-based products.
- . Uses environmentally friendly raw materials during its birth and emits no toxic gas when burned or buried after use.

:: GENERAL CHARACTERISTICS

- . Superior wear resistance
Exceeds 100,000 double rubs by wire screen
*ASTM D3597 Wyzenbeek
- . Anti-Bacterial/Anti-Microbial treatments (AATCC 147)
- . -20°F cold crack resistant (Fed. Standard 191 A)
- . Oil resistant (AATCC 130-2000) \
- . Sulfide stain resistant
- . Ultraviolet resistant
- . Anti-static finish

:: SUITABLE APPLICATIONS

- . Contract interiors
- . Office
- . Restaurant
- . Hospitality
- . Healthcare
- . RV/Marine interiors



FLOCK TEX, Inc.
200 Founders Dr.
Woonsocket, RI 02895
Tel: 401.765.2340
Fax: 401.765.4915
Toll Free: 800.556.7286
www.flocktex.com