POLYKEN®



Premium UL 181A-P & 181B-FX Listed Foil Tape



- Permanently seals seams in fiberglass duct board and flexible ducts for HVAC systems
- Suitable for use on rigid sheet metal ducts
- Durable seal for dryer ventilation

Features	Benefits
Aggressive cold weather acrylic adhesive	 Superior performance in all climate conditions Low odor Mold and mildew resistant
Kraft Release Liner	 Reduced environmental impact
• UL 181A-P & 181B-FX Listed	 Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
Low VOC Content	 Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values				
	Standard UOM	Metric UOM	Test Method	
Total Thickness w/o Liner	4.8 mils	0.12 mm	ASTM D-1000	
Foil Thickness	2.1 mils	0.05 mm	ASTM D-1000	
Adhesion to Steel	68 oz/in	7.4 N/cm	PSTC-101	
Adhesion to Backing	80 oz/in	8.8 N/cm	PSTC-101	
Tensile Strength	28 lb/in	49 N/cm	ASTM D-1000	
Application Temperature	-10 to 200 °F	-23 to 93 °C		
Operating Temperature	-25 to 325 °F	-32 to 163 °C		
Flame Spread	3			
Smoke Developed	0			
VOC Content	<1 g/L			

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

