


Insulation Jacketing Tape



- Backing:** Foil/Scrim/Kraft Paper Laminate
- Adhesive:** Synthetic Rubber
- Liner:** Unbleached Natural Kraft Paper
- Colors:** Aluminum

- Specifications:** Tested in accordance with UL723
- Standard Sizes:** 72mm x 46M

Applications

- Vapor barrier seal for insulation facing
- Sealing insulation and repairing in cooler/refrigeration applications

Features

- Foil/Scrim/Kraft Laminate Backing
- Synthetic Rubber Adhesive
- Low VOC Content

Benefits

- High strength and tear resistant
- UV, moisture, and mold resistant
- Non-solvent for less odor and low VOC content
- Super high tack, aggressive bond to surfaces
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.25 mils	0.235 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	7.66 N/cm	PSTC-101
Tensile Strength	35 lb/in	61.29 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
WVTR	>0.02 Perms		Mocon (100° F, 90% RH)
Smoke Developed	15		
Flame Spread	15		
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.