

# POLYKEN®

# 513W

## Thread Seal Tape



Backing: PTFE Film

Adhesive: N/A

Liner: N/A

Colors: White

Standard Sizes: 0.5" x 520"

### Applications

- Self-lubricating tape for wrapping threads & pipe connections making them easy to assemble and disassemble.
- Extends fatigue life of sealed connections and eliminates system contamination common with messy liquid and paste sealants.

### Features

- PTFE Film
- Made in USA

### Benefits

- Self-lubricates
- Easy to use
- Increases ease of assembly
- Unlimited shelf life

### Typical Test Values

|                   | Standard UOM   | Metric UOM     | Test Method |
|-------------------|----------------|----------------|-------------|
| Total Thickness   | 3.5 mils       | 0.089 mm       | ASTM D-1000 |
| Pressure Rating   | <10,000 psi    |                |             |
| Temperature Range | -450 to 500 °F | -267 to 260 °C |             |

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): Unlimited

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.



101 Oakley Street Evansville, IN 47710  
1-800-343-7875 Fax 1-800-328-4822  
www.berryglobal.com  
5/15/2023