


GMC

Admount® Graphic Arts Mounting Tape



Liner:74# Polycoated KraftLiner Side Adhesive:Acrylic (I632)Backing/Carrier:1 mil PET FilmAir Side Adhesive:Acrylic (I632)

Applications

 Graphic arts uses for wide format digital and photographic print mounting

Features	Benefits		
Acrylic Adhesive	 Acid-free and pH neutral Smooth coating for even application UV Resistant 		
Polyester Film Carrier	Support for aid in processing and applicationConformable		
74# Polycoated Kraft Liner	 Good stay-flat and moisture resistance 		

Typical Test Values

	Standard UOM	Metric U	OM	Test Method	
Overall Thickness (w/liner)	8.7 mils	0.221	mm	PSTC 133	
Air-Side Adhesive Thickness	1.1 mils	0.028	mm	PSTC 133	
Carrier Thickness	1.0 mils	0.025	mm	PSTC 133	
Liner Side Adhesive Thicknes	1.1 mils	0.028	mm	PSTC 133	
Liner Thickness	5.5 mils	0.140	mm	PSTC 133	
Adhesion to Steel (Air Side)	40 oz/in	4.38	N/cm	PSTC 101 Mod	
Adhesion to Steel (Liner Side	40 oz/in	4.38	N/cm	PSTC 101 Mod	
Shear Strength	>7 Days			PSTC 107 Mod	
Laminating Temperature	68 to 100 °F	20 to 38 °C			
Service Temperature	-30 to 220 °F	-34 to 10	D4 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complex with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation forwhich Berry Global assumes any legal responsibility.

