


5000M-74

Differential Double-Coated Tape



74# Polycoated Kraft Liner:

Liner Side Adhesive: **Rubber (1915)**

Backing/Carrier: 0.5 mil PET Film

Rubber (1917) Air Side Adhesive:

Applications

- Bonding to a wide variety of PU and PE foams, felt, General purpose bonding uses cork, rubber, and sponge materials
- Splicing applications
- Weatherstripping

- Gasket, insulation, light shielding, and sound damping uses

Benefits

Features

| • | Differential Rubber Adhesive System | • | Air-side offers exceptional high tack | |
|---|-------------------------------------|---|--|--|
| | | • | Liner-side well-suited for general purpose use | |
| • | Polyester Film Carrier | • | Support for aid in processing and application | |
| | | • | Conformable | |
| • | 74# Polycoated Kraft Liner | • | Conformable and good dimensional stability | |

Typical Test Values

| | Standard UOM | Metric UOM | Test Method |
|--------------------------------|--------------|-------------|-------------------------------|
| Overall Thickness (w/liner) | 8.7 mils | 0.221 mm | PSTC 133 |
| Air-Side Adhesive Thickness | 1.4 mils | 0.036 mm | PSTC 133 |
| Carrier Thickness | 0.5 mils | 0.013 mm | PSTC 133 |
| Liner Side Adhesive Thickness | 1.3 mils | 0.033 mm | PSTC 133 |
| Liner Thickness | 5.5 mils | 0.140 mm | PSTC 133 |
| Adhesion to Steel (Air Side) | 145 oz/in | 15.86 N/cm | PSTC 101 Mod - 1 mil PET |
| Adhesion to Steel (Liner Side) | 125 oz/in | 13.68 N/cm | PSTC 101 Mod - 1 mil PET |
| Adhesion to Steel (Air Side) | 230 oz/in | 25.16 N/cm | PSTC 101 Mod - 2 mil Alu Foil |
| Adhesion to Steel (Liner Side) | 220 oz/in | 24.07 N/cm | PSTC 101 Mod - 2 mil Alu Foil |
| Shear Strength | >24 Hours | | PSTC 107 Mod |
| Laminating Temperature | 68 to 100 °F | 20 to 38 °C | |
| Service Temperature | 30 to 150 °F | -1 to 66 °C | |

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation forwhich Berry Global assumes any legal responsibility.

