


HI/LO 4747

M-Tak[®] Differential Double-Coated Tape



Carrier: Polyester Film

Adhesive: Differential Synthetic Rubber (HM809)

Liner: 54# SC Kraft with Finger-Lift Edge™

Product Constructions Available
Number TW TL AW
4747 1.75" 1800ft 1.5"

Applications

Labels and business forms

Signs, posters, and advertisements

Aggressive bond to low surface energy substrates

Mailer and envelope sealing

POP Tags

Features Benefits

•	Synthetic Rubber Adhesive	High adhesion for secure, permanent bond	
		Good cold-temperature performance	
		 Excellent bond to LSE substrates 	
•	PET Film Carrier	 Provides support and structure for added stability 	
		 Conformable 	
•	Finger-lift Edge Liner	Easy to start, easy to use	
		Liner removes clean and smooth	

Typical Test Values

	Standa	ard UOM	Metric UOM	Test Method
Tape Thickness (w/o liner)	7.7	mils	0.196 mm	ASTM D-1000
Liner Thickness	3.2	mils	0.081 mm	ASTM D-1000
Air-Side Adhesive Thickness	2.7	mils	0.069 mm	ASTM D-1000
Liner Side Adhesive Thickness	4.5	mils	0.114 mm	ASTM D-1000
Overall Thickness	10.9	mils	0.277 mm	ASTM D-1000
Adhesion to Steel (Air Side)	50	oz/in	5.47 N/cm	ASTM D-3330
Adhesion to Steel (Liner Side)	105	oz/in	11.49 N/cm	ASTM D-3330
Application Temperature Range	30 to	140 °F	4 to 40 °C	
Operating Temperature Range	-30 to	165 °F	-29 to 71 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

