


Heat Reflective FR Wire Harness Tape



Backing: Aluminum Foil/Fiberglass Composite Fabric

Adhesive: High Temperature Silicone

Colors: Metallic

Standard Sizes: 1.25" x 36yd, 2" x 36Yd
*Available with pinked or straight edge

Specifications: FAR 25.853(a) & FAR 25.855(d)

Applications

- Heat shielding
- Abrasion guard
- High temperature continuous wrap

Features

- Aluminum/Fiberglass Backing
- Silicone adhesive
- Flame retardant

Benefits

- Conformable & hand tearable
- Reflects heat
- Abrasion resistant
- High strength
- High temperature performance
- Good long-term adhesion
- Meets FAA flammability requirements

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	6.5 mils	0.165 mm	ASTM D-1000
Adhesion to Backing	45 oz/in	4.92 N/cm	PSTC-1
Adhesion to PVC	35 oz/in	3.83 N/cm	PSTC-1
Tensile Strength	144 lb/in	252.18 N/cm	ASTM D-1000
Unwind Force	45 oz/in	4.92 N/cm	PSTC-8
Flame Resistance	Self Extinguishing		ISO-3795
Temperature Rating	200 °C		
Shelf Life at 25°C	12 Months		

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.