


853

PE Vapor Barrier Sealing Tape



Backing: Low Permeability PE Film

Adhesive: Acrylic Liner: N/A

Colors: Red

Standard Sizes: 96mm x 55m

Applications

- Seaming vapor barrier films and underlayment materials including 10, 15, and 20 mil films
- Splicing and seaming heavy-weight materials subjected to high abrasion and stress
- Concrete underlayment applications including patch, repair, and sealing penetrations coming through the slab
- Polyethylene splicing and patching

Features Benefits

 Polyethylene Film Backing 	 Tough and durable 	
	 Exceptional vapor barrier properties 	
	 Conformable 	
Acrylic Adhesive	 Aggressive bond to polyethylene and other vapor barrier materials 	
	 Moisture-resistant, resists mold growth 	
	 Excellent all-temperature performance 	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	6.0 mils	0.152 mm	ASTM D-1000
Adhesion to Steel	120 oz/in	13.13 N/cm	PSTC-101
Tensile Strength	13.6 lb/in	23.82 N/cm	ASTM D-1000
Elongation	900%		
Application Temperature	0 to 175 °F	-17 to 80 °C	
Operating Temperature	-22 to 212 °F	-30 to 100 °C	
Permeance	0.03 Perms		ASTM F1249

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is validable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

