
POLYKEN[®]

Multi-Purpose PE Tape



Backing: Polyethylene Film **Adhesive:** Synthetic Rubber

Liner: N/A

Colors: Red, White, Black, Silver, Teal, Blue, Orange,

Clear, Pink*, Green*

Specifications: Meets NFPA-701, Tested in Accordance

to ASTM E84

Standard Sizes: 48mm, 72mm, 96mm x 55M

Applications

- Abatement industry: hang and patch poly sheeting, seal waste disposal bags, etc.
- Labeling and color coding
- Short-term masking for stucco and plaster
- Bundling, wrapping, and repairs
- Temporary surface protection
- Convention industry bundling carpet, securing poly carpet protection, color coding, etc.
- Seam and patch shrink wrap for indoor/outdoor storage of marine, RV, and other equipment
- Film-to-film splicing
- Dissimilar metal tape

Features Benefits

Polyethylene Film Backing	 Conformable and flexible Excellent durability and solvent resistance Low elongation for consistant surface bond Pinked Edge available for hand tearability
Synthetic Rubber Adhesive	 High tack for good quick stick Excellent shear strength Repositionable and clean removal from many surfaces
Low VOC, <u>Contains no heavy metals</u> (such as lead and chromium)	Environmentally friendly & safe to use.

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.0 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	25 lb/in	43.78 N/cm	ASTM D-1000
Permeance	0.11 US Perms		ASTM F1249
Application Temperature	30 to 160 °F	-1 to 71 °C	
Operating Temperature	20 to 200 °F	-7 to 93 °C	
Elongation	85%		
Flame Spread Index	0		
Smoke Developed Index	30		

Recommended Storage Conditions: 60-80 °F at 40-60% RH * Subject to availability and minimum order Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation forwhich Berry Global assumes any legal responsibility.

