


360

Polypropylene Water Filter Outerwrap Tape



Backing: Unidirectional Polypropylene

Adhesive: Permanent Acrylic (A100)

Liner: N/A

Colors: Blue, White

Specifications: Registered with NSF through Supporting Material

information (AESOP 6928).

Size Options: Incremental sizes 1.5" - 52" x LY

Applications

 Seamless outer wrap for reverse osmosis water filters - replaces spiral wrapped PVC tape

Features	Benefits

•	Unidirectional Polypropylene	•	Excellent dimensional stability & high strength
		•	Smooth, easy unwind
		•	Moisture and abrasion resistant
		•	Bright, glossy, opaque finish
•	Acrylic Adhesive	•	Permanent adhesion for long term protection
		•	Excellent temperature resistance

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	5.0	mils	0.127	mm	PSTC-133
Substrate Thickness	4.0	mils	0.102	mm	PSTC-133
Adhesion to Steel	45	oz/in	4.92	N/cm	ASTM D-3330
Tensile Strength	150	lb/in	262.69	N/cm	ASTM D-3759
Elongation	37%				
Application Temperature	65 to 120 °F		18 to 49 °C		
Operating Temperature -40 to 250 °F		-40 to 121 °C			

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

