


## **High Temp PVC Fineline Masking Tape**



Backing: **PVC Film** 

Adhesive: Rubber (R406)

N/A Liner:

Lt Blue, Medium Blue (Matte) Colors:

**Specifications:** N/A

Size Options: Incremental sizes 0.118" - 47.5" x 108Ft

## **Applications**

- Masking color separations on finished metals and plastics (TPO & RIM) fascia and trim
- High temperature bake cycles (280 °F up to 45 min)\* Autobody aftermarket fineline color separations
- OEM paintline and powerwash operations
- Short-term outdoor masking

Clean room paint masking

**Features Benefits** 

PVC Film Backing	<ul> <li>Solvent and moisture resistant</li> </ul>			
	<ul> <li>Handles compound and tight radius curves</li> </ul>			
	Crisp, fineline edge			
	Non-glare matte finish			
<ul> <li>Rubber Based Adhesive</li> </ul>	<ul> <li>Good high temperature performance</li> </ul>			
	<ul> <li>Staining and ghosting resistant</li> </ul>			
Clean-cut Plastic Core	Recyclable and clean - no dust or contaminants			

**Typical Test Values** 

	Standard UOM		Metric UOM		Test Method
Total Thickness	5.5	mils	0.140	mm	PSTC-133
Substrate Thickness	4.0	mils	0.102	mm	PSTC-133
Adhesion to Steel	15	oz/in	1.64	N/cm	ASTM D-3330
Tensile Strength	15	lb/in	26.27	N/cm	ASTM D-3759
Elongation	100%				
Application Temperature	60 to 120 °F		16 to 49 °C		
Operating Temperature	40 to 280 °F		4.4 to 138 °C		

<sup>\*</sup>Room temperature demask recommended

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility

