


Utility Preservation & Sealing Tape



LDPE Film Backing:

Adhesive: Rubber (R400)

N/A Liner:

Colors: Clear, White

Specifications: N/A

Size Options: Incremental widths 1/4" - 46" x 108ft

Applications

Sealing, patching, and splicing polyethylene sheeting or shrink film used for construction, mobile homes, outdoor equipment, and material storage

General purpose patch and repair

• Used in suncatcher production to secure frames during epoxy painting - allows for a clear, defectfree surface

Features Benefits

LDPE Film	 Conformable for irregular surfaces
	Abrasion resistant
	 Moisture, solvent, and chemical resistant
Rubber Adhesive	Good guick stick

- Good quick stick
 - · Sticks aggresively to most surfaces
 - Smooth unwind

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	8.0	mils	0.203	mm	PSTC-133
Substrate Thickness	7.0	mils	0.178	mm	PSTC-133
Adhesion to Steel	25	oz/in	2.74	N/cm	ASTM D-3330
Tensile Strength	15	lb/in	26.27	N/cm	ASTM D-3759
Elongation	450%				
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	50 to 190 °F		10 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

