


Insulation Jacketing Tape



Backing:	Embossed PVC Film
Adhesive:	Acrylic
Liner:	Paper
Colors:	White
Specifications:	N/A
Standard Sizes:	3" x 50Yd

Applications

- Seaming and patching vinyl-faced fiberglass insulation materials.
- Maintaining vapor barrier integrity for water heater insulation blankets.

Features

- Embossed PVC Film
- Acrylic Adhesive

Benefits

- Conformable and durable
- Excellent moisture barrier properties
- Provides a strong long-term bond
- No flagging or lifting
- Excellent all-temperature performance

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.6 mils	0.117 mm	ASTM D-1000
Adhesion to Steel	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	7 lb/in	12.26 N/cm	ASTM D-1000
Elongation	100%		
Operating Temperature	-40 to 225 °F	-40 to 107 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.