


Premium PE Film Tape



Backing:	Polyethylene Film
Adhesive:	Rubber
Liner:	N/A
Colors:	Clear, Black, Red, White
Specifications:	Meets DPM 871-2, 871-3, and 877-1
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Stucco and plaster masking
- General purpose outdoor masking
- Surface protection in aerospace, automotive, and manufacturing applications
- Bunding, wrapping, and repairs
- General purpose abatement applications such as hanging and patching PE sheeting, securing waste disposal bags, and more

Features

- Polyethylene Film Backing
- Natural rubber based adhesive
- Low VOC Content

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Withstands outdoor exposure and moisture
- High tack for a secure bond
- Repositionable and clean removal - no residue
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	8.0 mils	0.203 mm	ASTM D-1000
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC-101
Tensile Strength	21 lb/in	36.78 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
MVTR (96% RH, 100° F)	0.112 perms		ASTM D-3833
VOC Content	<2 g/L		
Elongation	70%		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the