


Utility Grade Carton Sealing Tape



Backing:	Polypropylene Film
Adhesive:	Synthetic Rubber
Liner:	N/A
Colors:	Transparent
Specifications:	Meets CFR21.B.175.105 for indirect food packaging
Standard Sizes:	48mm x 50M, 48mm x 100M

Applications

- Sealing light-weight packages
- Bundling and wrapping

Features

- BOPP Film Backing
- Rubber Adhesive

Benefits

- Strong and durable
- Abrasion resistant
- High tack for a secure bond to most corrugate
- No flagging or lifting
- Moisture & chemical resistant

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	1.54 mils	0.039 mm	ASTM D-1000
Adhesion to Steel	44 oz/in	4.81 N/cm	PSTC-101
Tensile Strength	22 lb/in	38.53 N/cm	ASTM D-1000
Elongation	165%		
Max Operating Temp	120 °F	48 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.