


## Polyethylene Electrical Tape



**Backing:** Polyethylene Film

**Adhesive:** Rubber

**Liner:** N/A

**Colors:** Black

**Specifications:** UL 510 Classified  
Meets DPM 881

**Standard Sizes:** 1" x 36Yd, 48mm x 33m

### Applications

- Electrical and maintenance applications
- Wrapping and waterproofing wire harnesses
- For use when PVC electrical tapes are not suitable or permitted
- Excellent replacement for the combination for the combination of splicing and friction tape

### Features

- Polyethylene Film Backing
- Natural rubber based adhesive

### Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Provides excellent dielectric strength
- Good performance indoors and out
- Strong adhesive for a secure watertight seal
- Suitable for use up to 11,500V
- Superior all-temperature performance

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	9.5 mils	0.241 mm	ASTM D-1000
<b>Adhesion to Steel</b>	31 oz/in	3.39 N/cm	PSTC-101
<b>Adhesion to Backing</b>	20 oz/in	2.19 N/cm	PSTC-101
<b>Tensile Strength</b>	17 lb/in	29.77 N/cm	ASTM D-1000
<b>Application Temperature</b>	-10 to 180 °F	-23 to 82 °C	
<b>Operating Temperature</b>	-40 to 180 °F	-40 to 82 °C	
<b>Elongation</b>	220%		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.