


POLYKEN[®] 3598B

Single-Coated Film Tape



- Backing:** 1 mil Polyester Film
- Adhesive:** Medical-Grade Acrylic (M121)
- Liner:** 74lb bleached polycoated kraft, silicone treated on one side

Applications

- Medical device assembly
- Medical device attachment
- Diagnostic test strips and devices
- Reinforcing applications

Features

- PET Film Carrier
- Acrylic Adhesive
- 74lb Kraft Liner

Benefits

- Provides dimensional stability and stiffness
- Resists tearing and abrasion
- High tack and good shear properties
- Resists plasticizer and oil migration
- Easy to die cut and process
- Dimensionally stable and moisture resistant

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	8.3 mils	0.211 mm	PSTC 133
Adhesive Thickness	1.4 mils	0.036 mm	PSTC 133
Carrier Thickness	1.0 mils	0.025 mm	PSTC 133
Liner Thickness	5.9 mils	0.150 mm	PSTC 133
Adhesion to Steel	48 oz/in	5.25 N/cm	PSTC 101 Mod

Product Safety

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be non-cytotoxic, and non-irritating.

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

