


3920R

Polypropylene Surface Protection Tape



Backing: Release-coated Embossed Polypropylene

Adhesive: Rubber (RF409)

Liner: N/A

Colors: Clear, Tinted Red

Specifications: N/A

Size Options: Incremental sizes 1/4" - 48" x 108Ft

Applications

- Graphics protection for skis, snowboards, and other outdoor equipment where crisp graphics are critical
- Screen and direct print (130 °C press temp)

Protective mask for surfaces during lamination, molding, or machining where clean removal

is critical

Features Benefits

	i catalos	Benefits		
Ī	Embossed polypropylene backing	Conformable and stretchy		
		 Transparent for easy inspection of surfaces 		
		 Abrasion and moisture resistant 		
		 Release coated for smooth, consistent unwind, 		
		even at wide widths		
	Rubber Based Adhesive	 Does not lift during molding or shaping 		
		 Smooth, easy unwind 		
		 Removes cleanly from most surfaces - no 		

- Removes cleanly from most surfaces no residue upon removal
- Excellent extreme temperature performance

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	4.2	mils	0.107	mm	PSTC-133
Substrate Thickness	3.7	mils	0.094	mm	PSTC-133
Adhesion to Steel	15	oz/in	1.64	N/cm	ASTM D-3330
Tensile Strength	14	lb/in	24.52	N/cm	ASTM D-3759
Elongation	700%				
Application Temperature	50 to	120 °F	10 to 4	9 °C	
Operating Temperature	-40 to 325 °F		-40 to163 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 18 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchanitability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

