



## LSE & Low VOC Acrylic Transfer Tape

Rele	ase Liner	se Liner Liner:		84# Polycoated Kraft	
Adh	esive	Adhesivo	9:	Acrylic	(1626)
		Specifica	ations:	Adhes Specs	ive meets various Automotive
	1	Applica	tions		
<ul> <li>Bonding foam to rigid and flexible</li> <li>Laminating and mounting to ABS, paints, TPO, PE, PP, PET, and m energy materials</li> </ul>	powder-coa				bonding properties ding applications
Features					Benefits
Acrylic Adhesive			<ul><li>Low</li><li>High</li></ul>	peel and	ck ow flammability shear properties and low temperature performance
84# PC Kraft Liner			<ul> <li>Provides dimensional stability and aids in processing and application</li> <li>Moisture resistant</li> </ul>		
Typical Test Values					
	Standard	d UOM	Metric	UOM	Test Method
	4.0	mils	0.102	mm	PSTC 133
Adhesive Thickness					PSTC 133
Adhesive Thickness Liner Thickness	-	mils	0.168	mm	
	6.6 75	oz/in	8.21	N/cm	PSTC 101 Mod - 1 mil PET
Liner Thickness	6.6 75 109	oz/in oz/in			PSTC 101 Mod - 1 mil PET PSTC 16
Liner Thickness Adhesion to Steel (Air Side) Loop Tack Shear Strength (1" x 1" x 1Kg @ 72 °F)	6.6 75 109 >7	oz/in oz/in Days	8.21 11.92	N/cm N/cm	PSTC 101 Mod - 1 mil PET
Liner Thickness Adhesion to Steel (Air Side) Loop Tack	6.6 75 109 >7 68 to	oz/in oz/in	8.21	N/cm N/cm °C	PSTC 101 Mod - 1 mil PET PSTC 16

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com