




580

Polyethylene Screen Block Tape



- Backing:** LDPE Film
- Adhesive:** Acrylic (A100)
- Liner:** N/A
- Colors:** White, Black, Red, Blue, Yellow, Orange, Green
- Specifications:** N/A
- Size Options:** Incremental widths 1/4" - 54" x 108ft

Applications

- Border tape for screenblock applications - prevents ink from penetrating beyond the image area
- Covers pinhole and registration marks
- Block-out applications - adheres directly to the screen mesh allowing for multi-color printing

Features

- LDPE Film
- Acrylic Adhesive

Benefits

- Tough and conformable
- Available in 8 colors
- Excellent solvent and chemical resistance
- Good adhesion to surfaces
- Excellent long term bonding strength

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	5.5	mils	0.140	mm	PSTC-133
Substrate Thickness	4.5	mils	0.114	mm	PSTC-133
Adhesion to Steel	50	oz/in	5.47	N/cm	ASTM D-3330
Tensile Strength	11	lb/in	19.26	N/cm	ASTM D-3759
Elongation	400%				
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	-40 to 190 °F		-40 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F
 Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

