


## **General Purpose PVC Film Tape**



Backing: PVC Film

Adhesive: Rubber (R306)

Liner: N/A

Colors: Black, Brown, Purple, Red, Orange, White,

Yellow, Blue, Green

**Specifications:** A-A-1689B, Type II (supercedes PPP-T-66E,

Type 1, Class 2)

Size Options: Incremental sizes 1/4" - 48" x 108Ft

## **Applications**

- Color coding and striping
- Identifying safety equipment and hazards
- Aisle and floor marking

- Harness wrapping
- Duct and joint sealing
- Decorative packaging

Features Benefits

<ul> <li>PVC Film Backing</li> </ul>	<ul> <li>Conformable to irregular surfaces</li> </ul>		
	<ul> <li>Excellent solvent, chemical, moisture, and</li> </ul>		
	abrasion resistance		
	<ul> <li>Excellent for spiral wrapping</li> </ul>		
<ul> <li>Rubber Based Adhesive</li> </ul>	<ul> <li>Smooth, controlled unwind</li> </ul>		
	<ul> <li>Strong bond to smooth and irregular surfaces</li> </ul>		

**Typical Test Values** 

	Standard UOM		Metric UOM		Test Method
Total Thickness	6.0	mils	0.152	mm	PSTC-133
Substrate Thickness	5.0	mils	0.127	mm	PSTC-133
Adhesion to Steel	18	oz/in	1.97	N/cm	ASTM D-3330
Tensile Strength	18	lb/in	31.52	N/cm	ASTM D-3759
Elongation	250%				
Application Temperature	-14 to 140 °F		-10 to 60 °C		
Operating Temperature	-20 to 176 °F		-29 to 80 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80  $^{\circ}$ F Standard Shelf Life (at 25  $^{\circ}$ C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

