


4142U-74

Rubber Transfer Tape



Release Liner Liner: 74# PCK

Adhesive: Rubber (1924)

Specifications: Tested to numerous Automotive Specs

Applications

- Bonding to a wide variety of foams, felt, cork, rubber, and sponge materials
- Splicing applications
- Weatherstripping

- General purpose bonding uses
- Gasket, insulation, light shielding, and sound damping uses

Features Benefits

 Rubber Adhesive System 	 Offers exceptionally high tack and high peel 		
	 Excellent shear strength 		
	 Well-suited for general purpose bonding to 		
	medium and high energy substrates		
	 Designed for bonding to various foams, as well as 		
	rough and porous surfaces		
	 Exhibits moderate bond to LSE substrates 		
 74# Polycoated Kraft Liner 	 Conformable and good dimensional stability 		

Suitable for die-cutting and other slitting operations

	Standard UOM	Metric UOM	Test Method		
Overall Thickness (w/liner)	7.5 mils	0.191 mm	PSTC 133		
Thickness (Adhesive)	2.0 mils	0.051 mm	PSTC 133		
Liner Thickness	5.5 mils	0.140 mm	PSTC 133		
Peel Adhesion	190 oz/in	20.79 N/cm	PSTC-101 Method C		
Loop Tack Adhesion	199 oz/in	21.77 N/cm	PSTC 16 Method A		
Backing Release	9.96 g/in		PSTC-101 Method D - Modified		
Shear Strength (1" x 1" x 1 Kg)	> 7 days		PSTC 107 Mod		
Laminating Temperature	68 to 100 °F	20 to 38 °C			
Service Temperature	30 to 150 °F	-1 to 66 °C			

Typical Test Values

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use compiles with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

