


3591A

Transfer Adhesive



Adhesive: Rubber (I911)

Liner: 60lb super-calendered, silicone release treated on both sides

Applications

- Laminating paper, felt, sponge rubber, foam, and plastic
- Component assembly
- General mounting applications

Features

- Rubber Adhesive
- 60lb Release Liner

Benefits

- Superior adhesion to common substrates for assembly, laminating, and mounting
- Excellent quick stick
- Easy to die-cut and convert

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	5.3 mils	0.135 mm	PSTC 133
Adhesive Thickness	1.8 mils	0.046 mm	PSTC 133
Liner Thickness	3.5 mils	0.089 mm	PSTC 133
Adhesion to Steel	170 oz/in	18.60 N/cm	PSTC 101 Mod
Shear Strength	<24 hours		PSTC 107
Laminating Temperature	50 to 150 °F	10 to 65 °C	
Maximum Continuous Use	175 °F	79 °C	
Intermittent Use	200 °F	93 °C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.