

® polybale

The 5 star wrapping film for silage bales



5 star technology

Polybale is produced using specially selected high quality raw materials. These superior ingredients are directed to the film layer where they are most needed to ensure the production of an advanced stretch film with superior performance characteristics.

100% reliable 5 star blown co-extrusion production process

Our zero tolerance approach to quality ensures the production of a silage stretch film that delivers highly efficient bale wrapping of both round and square bales all day long.


Automatic thickness control

Thanks to continuous electronic monitoring of the film thickness throughout manufacture, Polybale has a uniform appearance at all stages of the wrapping process. These non-stop checks ensure the production of a consistently reliable film that provides trouble-free wrapping 24 hours a day.




® polybale


Polybale's high strength stretch and tear resistance helps to ensure 100% efficient wrapping of both round and square bales across a variety of crops (silage, haylage, alfalfa, lucerne) on all types of bale wrappers time after time.



High puncture and tear resistance



Improved Oxygen barrier



Bespoke blend of tack additives



Specification				
Width (mm)	250	360	500	750
Thickness (µm)	25	25	25	25
Length (m)	1800	1500	1800	1500
Colour	Green, Black, White, Olive			
Pallet Dimensions (cm)	108x108	100x125	108x108	100x125
Reels/Pallet	64	80	48	40
Pallet Height (cm)	± 128	± 165	± 165	± 165

Polybale is produced in an ISO 9001, ISO 14001 and OHSAS 18001 certified organisation.



www.polybale.com

a brand of **Berry**