

## UN SuperFlex Ø266 mm 11,3 ltr

**Product no:** 289 UN  
**Shape:** Round  
**Available lids:** 267 UN (Standard)



### VOLUME

Volume under lid:	11.3 l ± 120 ml	Volume brimful:	11.6 l ± 120 ml
-------------------	-----------------	-----------------	-----------------

### DIMENSIONS

External diameter top:	264.9 mm ± 1 mm	Height:	250.3 mm ± 1 mm
External diameter bottom:	239.3 mm ± 1 mm		

### WEIGHT

Weight:	342 g ± 10 g	Weight metal handle:	38 g ± 4 g
Weight plastic handle:	25 g ± 3 g		

### PERFORMANCE

**Stackability - dynamic:** Max: 37 kg top load on bottom container at 23°

**UN approval:** UN Group 2 and 3 solids with inside bag, PE min. gauge 150 (37.5 micron mm)

**Stacking tests**  
 The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

**Special:** 1 H2/Y11/S, homologation for solids with bag inside, weight 11 kgs. Certificate Bureau Veritas B-1154 13/10/04

### CLOSURE SYSTEM

**Lid type options:** Standard

**Closure type:** Flex-off

**Tamper Evidence type:** None

### HANDLE

**Standard handle:** Metal with roller grip, Flexible plastic hanging

### DECORATION

**Decoration available:** Dry Offset

**Decoration area offset:** 767 X 145 / 205 mm

### RAW MATERIAL (MECHANICAL PROPERTIES)

**Raw material options:** PP

**Masterbatch colours:** Colours according to Berry Superfos standard selected pantone colours.

**Hot temperatures:** The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.

**Cold temperatures:** Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.

### QUALITY SPECIFICATIONS

**Approvals:** All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

**Shelf life:** The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

**Quality information:** Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.

**Compliance and product suitability:** For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.