## Technical Datasheet

_						
SuperFlex Ø	1 <mark>94 mm 2</mark> 2191	,6 ltr				
Shape: Available lids:	-					
VOLUME						
Volume under lid: 2		2.6 l ± 30 ml	Volume brimful:		2.8	± 30 ml
DIMENSIONS						
External diameter top: 1		194 mm ± 1 mm	Heig	ght:	121 ו	mm ± 0.5 mm
External diameter bottom: 1		170.5 mm ± 1 mm				
WEIGHT						
•		93 g ± 5 g	Wei	ight metal handle: 18 g ± 1.8		± 1.8 g
Weight plastic handl	e:	6 g ± 0.6 g				
PERFORMANCE						
Stackability - dynamic: Max: 26 kg top load on bottom container at 23°   Stackability - dynamic: The stackability - dynamic at 22°C						
Stacking testsThe stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.						
CLOSURE SYSTEM	1			HANDLE		
Lid type options:		Membrane, Tamper Evidence, Standard		Standard handle: Optional handle:		Flexible plastic hanging Metal
Closure type:		Flex-off				
Tamper Evidence type: Ta		Tamper Evidence lid				
DECORATION						
Decoration available:		Dry Offset, IML				
		553 X 88/68 mm				
RAW MATERIAL (MECHANICAL PROPERTIES)						
Raw material options:		PP				
Hot filling: Masterbatch colours:		Up to 95° C				
Hot temperatures:		Colours according to Berry Superfos standard selected pantone colours. The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably,				
plastic packaging become flexible when subjected to hot filling temperatures and care must be relation to stacking immediately after hot filling. The Berry Superfos packaging must be tester with the actual product before approval for use at hot temperatures.				es and care must be taken in		
Cold temperatures	:	Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.				
	ATIONS					
Approvals: All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.						
		The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
Quality information:		Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
		For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
www.superfos.com		Specifications are subject to change without notice. Latest revision: 10-05-2019				