## Technical Datasheet

SuperFlex Ø Product no: Shape: Available lids:	297 mm 1 2460 Round 1122 (Stan 2442 (Stan 445 (Memb	dard) dard)					
VOLUME							
Volume under lid: 1		11.4 l ± 100 ml	Volume brimful:		12 l ± 100 m	12 l ± 100 ml	
DIMENSIONS							
External diameter top: 2		296 mm ± 3 mm	Height:		208 mm ± 1	208 mm ± 1 mm	
External diameter bottom: 2		266 mm ± 1 mm					
WEIGHT							
Weight: 3		323 g ± 10 g	Weight metal handle:		38 g ± 3 g	38 g ± 3 g	
Weight metal handle with 4 roller grip:		45 g ± 5 g	-				
PERFORMANCE							
Stackability - dynamic: Max: 45 kg top load on bottom container at 23°							
Stacking tests The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.							
CLOSURE SYSTEM	1		H	ANDLE			
Lid type options:		Membrane, FlakeFree, Standard	St	andard handle:	Meta	al, Metal with roller grip	
Closure type:		Flex-off					
Tamper Evidence type:		None					
DECORATION							
Decoration available	:	Dry Offset, IML					
Decoration area offset:		858 X 135/165 mm					
RAW MATERIAL (MECHANICAL PROPERTIES)							
Raw material options:		PP					
Hot filling:		Up to 95° C					
Masterbatch colours:		Colours according to Berry Superfos standard selected pantone colours.					
Hot temperatures:		The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.					
<b>Cold temperatures:</b> Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.							
	CATIONS						
Approvals: All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.							
Shelf life:The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct su light, rain, very low temperatures or very high temperatures over a long period.							
Quality information:Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.							
Compliance and pro	duct suitability	For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.					
www.superfos.com		Specifications are subject to change without notice. Latest revision: 01-03-2024					