Technical Datasheet

	Hobbock Mem	obbock Membrane Lid 378 mm				
		1328 Round				
	DIMENSIONS					
	External diameter:	3	72.8 mm ± 3.5 mm	Height:	27 mm ± 0.5 mm	
	WEIGHT					
	Weight:	1	50 g ± 8 g			
	PERFORMANCE					
period of 2 months. Stackability de			period of 2 months. Stackabili	ty depends on many factors and the	material as stated below at 23°C over a above data is meant as an indication only. the viability of stacking and transportation.	
	CLOSURE SYSTEM	OSURE SYSTEM				
	Closure type:		Peel-off			
	DECORATION					
Decoration available:		Dry Offset				
Decoration area offset:		190 mm				
RAW MATERIAL (MECHANICAL P			PROPERTIES)			
	Raw material options:		PP			
	Masterbatch colours:		Colours according to Berry Superfos standard selected pantone colours.			
Hot temperatures:			The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.			
Cold temperatures:			Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
	QUALITY SPECIFICATIONS					
Approvals:		All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.				
Shelf life:		The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
Quality information:		Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
Compliance and product suitability:		For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
	www.superfos.com		Specifications are su	bject to change without notice.	Latest revision: 18-02-2019	