Berry Superfos				Technical Datasheet	
SuperLift Extra Ø200 mm 4,6 ltr					
Product no: 4738 Shape: Round Available lids: 547 (Stan 4547 (Sta					
VOLUME					
Volume under lid:	4.6 l ± 23 ml	Vol	ume brimful:	4.7   ± 24 ml	
DIMENSIONS					
External diameter top:	200 mm ± 1 mm	iaH	ght:	201.1 mm ± 1 mm	
External diameter bottom:	$166 \text{ mm} \pm 1 \text{ mm}$	1 101			
WEIGHT					
Weight:	178 g ± 9 g	We	ight metal handle:	19 g ± 1.9 g	
PERFORMANCE		110		······································	
Stackability - dynamic: Max: 37 kg top load on bottom container at 23°					
Stacking tests	The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
CLOSURE SYSTEM			HANDLE		
Lid type options:	Standard		Standard handle:	Metal	
Closure type:	Flex-off				
Protective collar:	Yes				
Tamper Evidence type:	Tamper Evidence tab				
DECORATION					
Decoration available:	Dry Offset w. laquer, Dry Offset				
Decoration area offset:	550 X 147 mm				
RAW MATERIAL (MECHANICAL PROPERTIES)					
Raw material options: PP					
Hot filling:	Up to 95° C				
Masterbatch colours:	Colours according to Berry Super	Colours according to Berry Superfos standard selected pantone colours.			
Hot temperatures:	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
Cold temperatures:	Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.				
QUALITY SPECIFICATIONS					
Approvals:	All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.				
Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
Quality information:	considered acceptable in the indu	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.			
Compliance and product suitability: For all information related to food contact compliance and product suitability ask for the Declaration of					

Compliance and product suitability: For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.

 www.superfos.com
 Specifications are subject to change without notice.
 Latest revision: 14-09-2022